



Booth Mask Stick

Paint Booth protection mask.

CHARACTERISTICS

Booth Mask Stick is a water-based, sprayable masking that protects spray booth surfaces against paint overspray. It is safe for use on all non porous surfaces. It forms a film which does not completely dry at ambient temperatures and can be easily washed off with water or a pressure washer. Improves paint finish by reducing dust, and dramatically reduces booth cleaning times.

PRODUCT DATA

Form: Liquid

Sizes: 5 or 20 liters

Shelf life: 2 years

HANDLING

Application:

1. Clean or refinish booth walls in order to achieve optimum lighting conditions. Make sure surfaces are completely dry
2. Fill Spray Gun (nozzle size 1.9-2.2mm) with Booth Mask Stick and adjust pressure according to recommended equipment adjustment. Adjust booth temperature to 70 degrees F.
3. Apply a wet coat to all booth surfaces including glass and lights. Avoid runs, drips or beads. Let dry (approximately 10 minutes), then apply a 2nd coat. After 2nd coat dries, apply a 3rd coat to high overspray areas only. Allow surfaces to dry completely.

Removal:

1. Allow booth to cool to a temperature of 70 degrees or lower.
2. TURN OFF ALL POWER TO BOOTH LAMPS AND ELECTRICAL OUTLETS.
3. Using a hose or pressure washer, spray water onto all surfaces. Allow water to stand and soak in for five minutes.
4. Using a wash mitt or brush, scrub areas with extra heavy overspray. Some areas may require use of a scuff pad to break up any thick layer of overspray which would prevent water from penetrating. Rinse off remaining overspray.

5. Using compressed air, blow away water from all lights and glass surfaces. Allow booth to dry. Remove water from booth floor with squeegee. Make sure all surfaces are dry before re-applying Booth Mask Stick.

Recommended Equipment Adjustments:

HVLP: Spray pressure should be 2.7-3.1bar, nozzle size: 1.9-2.2mm

PRECAUTIONS

Booth Mask Stick may not be suitable for use on top of uncured paints such as cellulose or household paints especially if the room is heated to low bake temperatures. In these cases there could be some interaction of the paint film with the Booth Mask Stick. It is not suitable for use on steel or galvanized booth walls because repeated washing with water as part of the booth maintenance procedure can cause corrosion.

SAFETY ISSUES

The previously provided information is based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty can be inferred either from this information or from a verbal consultation.