



## **DUST KEEPER**

Floor dust binding agent

### **CHARACTERISTICS**

Dust Keeper is a water-based, sprayable floor coating designed to collect and contain airborne dust commonly found in paint booths. When applied to booth or shop floors, Dust Keeper keeps dust on the floor and off painted surfaces, so you get clear paint work. After painting, simply sweep up the collected dust and overspray then reapply Dust Keeper. With Dust Keeper there is no need to wet down the floor of the booth to control contaminants. This eliminates unwanted humidity, wet slippery floors and potential rust damage from continuously wet booth walls. Dust Keeper also helps reduce overspray build-up on floors and grates.

### **PRODUCT DATA**

Form: Liquid

pH value: 7.5-8.5

Density: 1g/cm<sup>3</sup>

Application: approx. 70-80m<sup>2</sup> per liter

Sizes: 5 or 20 liters

Shelf life: 2 years

### **HANDLING**

Application:

Dust Keeper is most effective when used on a clear, non-oversprayed floor. Use a pump spray to apply a light coat of Dust Keeper on the clean floor. If the floor has overspray build-up, apply heavier coats, more often. Maintenance: Sweep out collected contaminants as needed, reapply as needed. Removal: If necessary, hose out collected contaminants with water, this will remove Dust Keeper. Squeegee or force dry, repeat application. Effective up to 3 paint cycles.

### **SAFETY ISSUES**

The previously provided information is based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so variable that no warranty can be inferred either from this information or from a verbal consultation.