



FINISH RESTORER

Plastic care

CHARACTERISTICS

Refinish Restorer is a natural oil based product that restores the original color and shine to almost any plastic or varnished surface. Refinish Restorer achieves this through deep penetration into the micro pores of the surfaces, sealing them and filling the internal capillaries, leaving a rejuvenated surface when dry.

APPLICATION

Refinish Restorer provides long lasting protection for plastics, gelcoats, lacquers, chrome, Stainless-steel, aluminum (anodized), brass, and copper. Over time almost all plastic and varnished surfaces fade and take on a matte finish. This is due to exposure to UV light, weathering, environmental contamination, etc. Refinish Restorer penetrates deeply into the micropores of the surfaces and seals them, when dry. It restores the surface to the original color. Refinish Restorer is only for external use. DO NOT use it on rubber. It may discolor white surfaces due to its inherently yellowish color. Test on a small, non visible area before use.

PRODUCT DATA

Specific gravity: .85 g/cm³

V.O.C.: 620 g/l

Shelf Life: At least 3 years

Consumption: Approximately 10 to 20m²/l

HANDLING

1. Surfaces to be sealed need to be clean and free of oil and grease. Any yellowing or staining on gelcoat and other plastic surfaces should be removed with a cleaner. The surface should be thoroughly rinsed with water. Metallic surfaces should be thoroughly degreased. Application on white surfaces can result in a slight color change.
2. After initial treatment the surface should be thoroughly dried before the Refinish Restore is applied.
3. Refinish Restorer cannot be applied onto very warm surfaces or in direct sunlight.

4. Refinish Restorer is applied evenly, using a soft flat brush or a lint free cloth, until the pores are filled.
 5. Refinish Restorer should take effect 5 to 10 minutes after application. Any liquid Refinish Restorer can be brushed over a more porous area.
 6. After a maximum of 10 minutes any excess oil should be removed with an absorbent lint free cloth or a soft pad, otherwise it can only be removed with a suitable remover, such as turpentine.
 7. If necessary repeat steps 4-6.
 8. When a high degree of shine is required, the surface treated can be polished with a non abrasive wax.
 9. Metallic surfaces are not very porous and must therefore be treated with a very fine wire wool soaked in Refinish Restorer. Excess oil must be removed after about 15 minutes. The surface can then be polished with a lint free cloth for a greater shine.
- Cleaning: Use Turpentine

PRECAUTIONS

The previously provided information is based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so variable that no warranty can be inferred either from this information or from a verbal consultation.